

Material Safety Data Sheet



Emergency Telephone: 1-800-828-9528 at Buffalo, Mo USA			
Identification: Concrete Remedy Internal Deep Seal Product Code: DS	Hazard Rating 4 – Extreme 3 – High 2 – Moderate 1 – Slight 0 – Insignificant	Fire 0 Health 1 Reactivity 0 Special Hazard 0	
Chemical Identity Information			
Proprietary mixture containing silicates, bonding catalysts and inerts. This product is not considered to be or to contain hazardous chemicals based on evaluations made by our company under the OSHA Hazard Communication Standard, 29 CFR 1910.1200			
Physical Data			
Appearance: Clear Liquid Odor: None Boiling point: 212 degrees F. Vapor Pressure: Unknown		Solubility in water: Complete Specific Gravity: 1.094 PH (1% solution) 8.96	
Fire and Explosion Data			
Flash Point: Flammability: Extinguishing Media: Unusual Fire or Explosion Hazard:		Non Flammable - Does not flash N/A N/A N/A	
Health Hazard Data			
Contains no hazardous materials as defined by OSHA and ACGIH.			
Eye(s): Skin: Ingestion:		May cause irritation and redness. May cause redness. Non-Toxic, may cause Gastro-Intestinal problem.	
Transport Information			
DOT UN Status: This material is not regulated hazardous material for transportation			

Material Safety Data Sheet

Emergency and First Aid Procedures	
Eye Contact:	Flush with cool clean running water for at least 15 minutes. If irritation persists, get medical attention.
Skin Contact:	Flush exposed area with clean, running water for at least 15 minutes. If irritation persists, get medical attention.
Ingestion:	Do not induce vomiting. Dilute with large amounts of water and weak vinegar or orange juice. Get medical attention immediately.
Special Protection Information	
Protective Gloves:	Rubber gloves recommended
Eye Protection:	Goggles recommended
Respiratory Protection:	None
Local Exhaust:	Good ventilation
Other Equipment:	None
Reactivity Data	
Incompatible Materials:	Do not mix with other chemicals
Stability:	Stable
Hazardous Polymerization:	Will not occur
Hazardous Decomposition:	None
Spill or Leak Procedures	
With small spills or leaks use absorbent material such as sawdust, vermiculite or sand. Larger spills dilute with large amounts of water, before flushing to sewer or drain according to local, state and/or federal regulations.	
Special Information	
Keep container closed when not in use. Store away from heat and do not freeze. Keep out of reach of children.	
The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and accept no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal and local laws. All chemicals may present unknown health hazards and should be used with caution.	

Prepared July 21, 2004